

Security devices


1 StereoVision 🔧 *




2 Contactmats/IR sensors*




3 Hangsensor*



4 Weightsensor*




5 Failsecure*














Maintenance

Caution! Don't use water near the drive units and controlboxes.Warning! Switch OFF the power supply of the Tourlock 180+90 during maintenance or other work.

Daily: Check daily the functionality of the Tourlock 180+90.

Weelky: Clean the anodised, stove enamelled and/or stainless steel surfaces with a wet cloth.

Monthly: Clean the anodised, stove enamelled and/or stainless steel surfaces with a wet cloth and a non aggressive soap.

Vacuum clean all the brushes.

Yearly: The Tourlock 180 + 90 needs a major maintenance check once a year. This has to be done by Boon Edam B.V. or

approved agents. This applies as well for repairs.

Dealer

For further information: consult the operating manual.

Instructioncard Tourlock 180 + 90

Safety- and users instructions

Control panel*

Security devices

Maintenance

Explanation of the symbols

Secured side



max. 3x

Doorset rotates 180°



Doorset completes 180°-cycle



Max. 3 Authorizations

Authorization



Doorset rotates manually



Passage possible within 9 seconds



Doorset will be blocked in the failsecure mode

Max. admissible weight of 110kg,



Acoustic signal

No power supply



Doorset is locked

(Weightsensor)

Doorset reverses



Option



Check the emergency- and safety devices and the general function of the Tourlock 180 + 90 daily!









Safety- and users instructions

A. The Tourlock 180 + 90 safety devices

1 Safety Rail Bent wall (SRB)









B. The workingprinciples of the Tourlock 180+90 with authorisation system


1 One authorized user




2 One authorized user (from secured side) one unauthorized user (from non secured side) or the opposite




3 One authorized user and one unauthorized user, from one side



4 Two authorized users (from secured and non secured side)




5 Two successively authorized users (from one side)




C. The signallamps on the Tourlock 180 + 90

1 Green illuminates (after authorisation)




2 Green illuminates continuously (when free entry or exit is enabled)



3 Red flashes (in all alarm situations and sensor activations)




4 Red illuminates continuously




Control panel*


1 One person in




2 One person out




3 Free in



4 Free out



5 Locking (possible in all positions)



6 Alarm/Buzzeralarm (in all alarm situations and sensor activations)



7 Reset

